

RGL12

SINGLE LEG ADJUSTABLE WEBBING RESTRAINT LANYARD RGL12



The RGL12 is an adjustable restraint lanyard and acts as a leash for an operative working at height.

The adaptability of the product ensures that the correct length can be selected for the task in hand. It is important to understand the principles of “fall-restraint” as the RGL12 can only be used for fall restraint, as there is no shock absorption built into the system. If there is any possibility of an operative stepping/falling over an exposed edge, or falling through a fragile surface, a fall arrest product should be used.

The 37kN webbing used in the manufacture provides greater strength compared to other webbing and systems. The RGL12 should never be used to extend another fall arrest product.

EN 354:2010

Material:	26mm RIDGE Protect anti-bacterial polyester*
Fittings:	Steel adjusters only. Supplied without connectors unless stated otherwise
Max arrest force:	Restraint only - Not to be used as fall arrest
Length(s):	0.7m - 1m 0.9m - 1.5m 1.2m - 2m (including connectors) (based on using 2 x RGK1s)

FEATURES



Steel Adjusters



* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RIDGEGEAR LIMITED

Nelson Street, Leek, Staffordshire, ST13 6BB

+44 (0)1538 384 108

sales@ridgegear.com

ridgegear.com



RGK1

17mm Steel Screwgate Karabiner

RGK1

- › Screwgate closure which must be closed manually
- › Used for rope access, fall arrest and rescue applications
- › Basic universal karabiner used
- › Individually serialised for complete traceability and inspection control

EN 362:2004

Material:	Steel
Plating:	Zinc
External length:	107mm
Gate opening:	17mm
Closure type:	Screwgate
MBS:	23kN
Weight:	160g

